

CUCM

Route Patterns, Lists and Groups

Route pattern
Match dialed numbers
Digit manipulation
Points to a route list

Route List
Ordered list pointing to Route-groups

Route Group
Performs digit manipulation
Points to gateways
The digit manipulation actually occurs (bound) on the route-list


Route Pattern Wildcards
@ = all NANP
X = any single digit
! = one or more digits 0-9
? = zero or more of the preceding digit
+ = one or more of the preceding digit
[] = enclose a range
- = used between brackets to denote a range
. = discard digit identifier
= end of dialing sequence
\ = escape character (used with + dialing)

Called Number Manipulation
DDI (i.e. pre-dot)
Mask (can add, delete or replace)
Prefix (add)

Calling Number Manipulation
External number mask
Calling party transformation mask
Prefix (add)

Digit Manipulation
If using more than one method in a route pattern or route-group, compounding takes place in order
Can take place in route pattern or route group (route list)
Use on route groups when different digit manipulation is required on each Gateway
Route lists supersede route patterns
If route pattern has pre-dot and route-list has a manipulation as well, the calling number displayed on the phone will be pre-dot
Called and Calling number manipulations are mutually exclusive. For instance, calling manipulation can occur on the route pattern and called on the route list

Local Route Group



Calling and Called Party Transformation Patterns (egress)

Calling Party
Calling number is modified as call is sent out Gateway
Uses a Partition and CSS that gives access to the translation pattern.
Other methods depend on the called number. Transformation patterns occur irrespective of called number.
Transformation pattern overrides any other modification (wins over RP, RL)
If different calling number modifications are needed based on called number (subscriber, international, etc) use the RP, RL method not transformations.
Use transformation pattern when calling number modification needs to be based on locale/Gateway

Called Party
Called party transformations are usually used when a number is globalized to modify it to a value that the PSTN can route. Frequently, the + is stripped
Recommended practice is to use a name in the PT/CSS that distinguishes this PT/CSS from others. Example: CSS-ANI-GW-HQ
For inbound calls (PSTN to IP Phone) phone calling transformation pattern CSS is used. No called transformation since phone is final destination
For outbound calls (IP Phone to PSTN), Gateway transformation patterns (both calling and called) are used

Calling and Called Party Transformations
Destination party always invokes transformation pattern

Example Calling Party Transform Pattern Table

Calling Party Transformation Pattern	Partition	Digit Manipulation	Calling # Type
XXXX	PT-ANI-SJC-GW	Prefix 408777	subscriber
XXXX	PT-ANI-SJC-GW	Prefix 415888	national
XXXX	PT-ANI-SFO-GW	Prefix 415888	subscriber

Plus Dialing

Purpose is to universally use full E164 formatted numbers
Dependant on globalization/localization
Must have route pattern that matches the + character
Use the Called Party Transformation Pattern and CSS to Example - +1415.1 PT-DNIS-GW-HQ
DDI PREDOT
Type= Subscriber
CSS= CSS-DNIS-HQ-GW
Dial peers strip the + character from the calling number since it's an illegal field in the IOS version in the lab. Re-insertion may be necessary

Globalization/Localization (ingress)

Example - call comes into SF gateway with ANI of 415 555 1212

May want to store the ANI of missed/received calls in a globalized format (E164) like +1 415 555 1212
May want to display the ANI in localized format like 555 1212

Globalization
Purpose is to store the number in globalized format
Globalize the number at the Gateway using Incoming Calling Number Prefix
Example - type subscriber: prefix +1415
Affects the received/missed called directory on the phone
Destination always invokes calling party transformation so for ingress, this is done on the phone

Localization
Purpose to display the number in a localized format
Localization of the incoming calling number to display the globalized number is done on the phone calling party transformation using the CSS. Example - +1415.1 DDI-PREDOT
Affects the displayed number on the phone

Dial Plan and Call Routing Notes

Calling number manipulation for plus dialing
Goal is to add +1 to missed calls but have ringing display localized (i.e. no + and proper ANI length based on calling number)
missed - use calling party transformation
ringing - use incoming calling party settings on Gateway

Translation Patterns
Can be used to manipulate digits on incoming calls. Example would be a MGCP Gateway where digit stripping is not possible and significant digits cannot be used on CUCM for whatever reason.
Example: Translation Pattern : 6178631XXX
Called Party Transformations
Called Party Transform Mask : 1XXX

Globalizing/Localizing Internal Calls
Create a PT strictly for the phones - assign all phones to this partition
Create a translation CSS - assign the phone PT
Add a PT for each GW
Add this PT to the CSS on each phone
Add a translation pattern that adds a +1 to each

DN
PT=phone-pt
CSS=cas-tp

Translation Pattern
Pattern =XXXX
PT = pt-hq-tp
CSS = css-tp
Prefix digits = +1

Phone
PT=pt-hq-tp
CSS=cas-hq-int

Common IOS translation rules

Prepend + to any string
voice translation-rule 111
rule 1 /+? /+0/

Remove area code/prefix
voice translation-rule 222
rule 1 /... /

add area code/prefix (212 example)
voice translation-rule 333
rule 1 // /212/

just last 4 digits
voice translation-rule 444
rule 1 /...\$/ /1/

High Availability

AAR
Used for on cluster endpoint to endpoint communications when there is WAN congestion
Location or RSVP CAC uses PSTN to complete call
Since intracluster calls are normally 4 or 5 digits, called number must be expanded to match route pattern
Dedicated CSS for AAR. Example is lobby phone might not be able to make local calls but with AAR this is needed. AAR CSS applied on the device (phone)
The external number mask of the called party is used to replace the dialed digits
AAR group is set at the line level
Dial prefix (Predot instructions) are added on the AAR group
AAR must be enabled in call manager service parameters
AAR should not be used with TEHO

SRST
Two part process:
1. Phones must register with CME
2. Dial peers must exist on CME
Two methods on IOS router:
1. Call-manager fallback - easy but limited features
2. Telephony-service - more features
CUCM Configuration steps
1. Set SRST reference under system tab
2. Assign SRST reference to device pool
3. Reset the phone
4. Check that phone settings have SUB, PUB and SRST IP in correct order
See CME SRST section for more information

CFUR
If phone that is in the CUCM cluster tries to call a phone that is SRST mode, the SRST phone shows up as unregistered
Under DN in CUCM there are Call Forward Unregistered for both internal and external calls

Configuration steps

1. Enable AAR in service parameters
2. AAR PT/CSS
3. AAR specific RP
4. AAR group
5. External number mask
6. Restart CCM

SRST (CME)

When in SRST mode, appropriate dial peers, translations

CUCME/IOS

Dial Peers

Two type of dial peers: POTS and voice-network
POTS - PSTN, PBX, Telephone, etc.
Voice-Network - Gateway, CUCM, etc.

Dial peers and call legs

Inbound (POTS)
Incoming-called number - matches the called number from the phone. Normally use.
Direct-inward dial - looks for a destination pattern that matches the DNIS Port - physical port

Outbound (VOIP)
Destination pattern - matches the called number from the phone
Session-target - specifies the endpoint for the peer

Digit Manipulation
Digit Striping and Prefixes
POTS by default strips matching the destination pattern. To change this, use either no digit strip or prefix commands
No digit strip disables automatic digit stripping
Prefix adds digit in front of the dialed string

Forward Digits
Controls how many digits are stripped before the dialed string is passed on. Only supported on POTS interfaces

Number expansion
Used to expand an extension number into dialable number such as a full E.164 number. Not likely a lab subject so no detail included here

Voice Translation Rules
Translation rules are used to change ANI, DNIS or the numbering type of a call
A translation rule which can consist of multiple entries is created then applied to either the called or calling number
3 step process
1. Create voice translation rule
2. Apply rule to profile for either called or calling number
3. Apply to dial peer in either the incoming or outgoing direction

Voice Translation Rule Patterns

Wildcard	Definition
-	Any single digit
0 to 9, *, #	Any specific character
[0-9]	A range or sequence of characters
*	Match none or more
+	Match one or more
?	Match none or one

Basic Voice Translation Rule Examples

voice translation-rule 1
rule 1 /123/ /999/
! matches 123 and replaces with 999

voice translation-rule 2
rule 1 /0+ / /909/
! matches any combination starting with zeros (0,00, etc) and replaces with 909

Number Slice
Number slice is used when a portion of the matched number needs to be copied to the replacement

Character	Description
\	In the match pattern, indicates where to slice up the number
	In the replacement pattern, indicates where to copy the sets to keep
()	Indicates which sets in the matched number to keep

Character Usage

Character	Description
{a}	Keep expression 'a'
{b}	Ignore expression 'b'
{1}	Copy the first set into the replacement number

Format
/(x) y(z) /n1/2/

Split the matched number into three sets of x, y and z. The backwards slash indicates the places to slice up the number. The brackets indicate which sets to reuse in the replacement pattern. The w represents additional digits to be inserted into the replacement number

Two examples:

voice translation-rule 2
rule 1 /+? / /5555/ /9004423214111/
! starting with 7 then any 3 digits, keep 5555

voice translation-rule 3
rule 1 /+? / /3... / /32141/
! any four digits starting with three prepend a 3214 and keep the 3 and last three digits

MGCP

CUCM	IOS
Choose device, gateway	Task description
Choose model of router and MGCP	Command
The domain name must match the FQDN of the router. Choose the CUCM group. Select the module with the WIC and the subunit	Create ISDN PRI with needed timeslots and enable the MGCP service controller T1 0/0/0 pri-group timeslots 1-3,24 service mgcp
Configure the WIC. Select PRI and other options as needed.	Provide PRI back haul to CUCM interface Serial0/0/0:23 isdn bind-3 com-manager ccm-manager switchback immediate ccm-manager redundant-host 10.10.210.10 ccm-manager mgcp ccm-manager fax protocol cisco
	Provides redundant CUCM to MGCP service mgcp mgcp call-agent 10.10.210.11 service-type mgcp version 0.1 mgcp dtmf-relay voip codec all mode out-of-band mgcp fax t38 ecm mgcp bind control source-interface Loopback0 mgcp bind media source-interface Loopback0
	Enables MGCP service on router Mandatory command that points to CUCM Allows DTMF symbols to be sent out of band Fax t38 error correction Bind control and media to loopback

H.323 Gateway

CUCM	IOS
Add into CUCM using "h323 gateway" Device name should have IP address of Gateway	Interface Loopback 0 H323-gateway voip bind srcaddr 10.10.110.1
	Set source address for H.323
	Provide Codecs needed Voice class codec 1 Codec preference 1 g711u Codec preference 2 g729r8
	Set misc H.323 values Voice class h323 1 h225 timeout tcp establish 3
	Configure voice translation rules
	Configure dial peers for call routing

H.323 Gatekeeper

Gatekeeper resolves telephone number
Also accepts bandwidth requests
If enough bandwidth, GK sends destination IP back to requesting Gateway
A local zone is defined as a group of H.323 devices that a Gatekeeper controls. Can have multiple GK per zone for redundancy
GK's do not register with GK's in remote zones. Location request messages are sent
Technology prefix - tech prefixes are used to group by type or class or to define a pool of Gateways. These are used when no registered E.164 number matches the call

Gatekeeper

Task Description	Command
Define router as Gatekeeper and begin configuration	Gatekeeper
Create local zone named NY in domain cisco.com with RAS address 10.1.5.1 using port 1719	Zone local NY cisco.com 10.1.5.1 1719
Assign the 212 area code to the NY prefix	Zone prefix NY 212.....
Bring up gatekeeper	No shutdown
Create the default technology prefix for the gatekeeper	gw-type-prefix 1* default-technology
Applies CAC on calls outside of NY zone to 16 Kbps	Bandwidth interzone zone ny 16

Gateway

Task Description	Command
Select the interface	Interface loopback 0
Configure the loopback interface as the Gateway	H323-gateway voip interface
The gatekeeper-id must match the zone name	H323-gateway voip id ny
Optionally, name the Gateway for the Gatekeeper	H323-gateway voip h323-id ny@cisco.com
Dial-peer example with RAS target	Dial-peer voice 91 voip destination-pattern 9T

Register CUCM to Gatekeeper
CUCM
Device - Gatekeeper - Add IP address of GK
Device - H.225 Trunk - Add the trunk

CME
Under interface - h323-gateway voip